

## BT nastavená na Nikon

Odečet BT LR2  
pro D700 a D3 je identickýOdečet BT  
LR2 pro D300

[K]	[mired]	Δ [mired]	[K]	[CC]	Δ [K] (Camera->LR2)	Δ [mired] (Camera->LR2)	[K]	[CC]	Δ [K] (Camera->LR2)	Δ [mired] (Camera->LR2)
2 500	400.0		2 600	2	100	-15.4	2 850	17	350	-49.1
2 560	390.6	-9.4	2 650	1	90	-13.3	2 850	14	290	-39.7
2 630	380.2	-10.4	2 650	1	20	-2.9	2 850	12	220	-29.4
2 700	370.4	-9.9	2 700	0	0	0.0	2 900	10	200	-25.5
2 780	359.7	-10.7	2 800	0	20	-2.6	2 900	7	120	-14.9
2 860	349.7	-10.1	2 850	-1	-10	1.2	2 900	4	40	-4.8
2 940	340.1	-9.5	2 900	-2	-40	4.7	2 900	2	-40	4.7
3 030	330.0	-10.1	2 950	-3	-80	9.0	3 000	0	-30	3.3
3 130	319.5	-10.5	3 050	-5	-80	8.4	3 050	-1	-80	8.4
3 230	309.6	-9.9	3 100	-6	-130	13.0	3 150	-2	-80	7.9
3 330	300.3	-9.3	3 200	-6	-130	12.2	3 250	-2	-80	7.4
3 450	289.9	-10.4	3 350	-7	-100	8.7	3 350	-3	-100	8.7
3 570	280.1	-9.7	3 450	-8	-120	9.7	3 450	-4	-120	9.7
3 700	270.3	-9.8	3 550	-10	-150	11.4	3 550	-4	-150	11.4
3 850	259.7	-10.5	3 700	-11	-150	10.5	3 700	-5	-150	10.5
4 000	250.0	-9.7	3 850	-12	-150	9.7	3 850	-6	-150	9.7
4 170	239.8	-10.2	4 000	-13	-170	10.2	4 000	-6	-170	10.2
4 350	229.9	-9.9	4 200	-7	-150	8.2	4 200	0	-150	8.2
4 550	219.8	-10.1	4 350	-5	-200	10.1	4 400	2	-150	7.5
4 760	210.1	-9.7	4 550	-4	-210	9.7	4 600	3	-160	7.3
5 000	200.0	-10.1	4 800	-5	-200	8.3	4 800	3	-200	8.3
5 260	190.1	-9.9	5 050	-6	-210	7.9	5 050	1	-210	7.9
5 560	179.9	-10.3	5 300	-7	-260	8.8	5 300	0	-260	8.8
5 880	170.1	-9.8	5 600	-8	-280	8.5	5 600	-1	-280	8.5
6 250	160.0	-10.1	5 900	-7	-350	9.5	5 900	-1	-350	9.5
6 670	149.9	-10.1	6 250	-6	-420	10.1	6 200	0	-470	11.4
7 140	140.1	-9.9	6 650	-4	-490	10.3	6 600	2	-540	11.5
7 690	130.0	-10.0	7 050	0	-640	11.8	7 000	6	-690	12.8
8 330	120.0	-10.0	7 600	4	-730	11.5	7 540	11	-790	12.6
9 090	110.0	-10.0	8 300	8	-790	10.5	8 000	16	-1 090	15.0
10 000	100.0		9 100	12	-900	9.9	8 800	22	-1 200	13.6